



DC Fast Charging Wallbox

Key Features

CE Certified

Fully compliant with European regulations

Customized Power Modules

30KW, 60KW

Multiple Charging Standard Compliant

CCS-1, CCS-2, CHAdeMO, GB/T

OCPP Compatibility

OCPP1.6J and upgradable to OCPP2.0.1

Secure User Identification

Via RFID or Mobile App

Benefits

Easy configuration to any charging network

OCA & OCPI official member

OCPP 1.6J, OCPP 2.0.1

OCPP Smart Charging

Smart Load Balancing

Applications



Residential



Commercial



Fleet



Parking




Specification

Specifications are subject to change without notice.

Model/PN	IOC030HY2	IOC060HY2
Input Rating	3-phase 400V±15% AC, 45-65Hz	
Power Factor	≥0.99	
Efficiency	95%	
Power Output	30KW	60KW
Output Voltage	150V-1000V DC	
Output Current	100A MAX	200A MAX
Electrical Protection	Over current, Short circuit, Over voltage, Under voltage, Ground fault, Lightning Surge, Over temperature	
Display	8" TFT LCD touch screen	
Supporting Language	English, Spanish, or other languages required	
User Authentication	RFID Card, Mobile App, Remote Access	
Push Buttons	Emergency stop	
Charge Mode	Alternately	Simultaneously
Charge Option	Charge by duration, by energy, by amount	
Operating Temperature	(-30℃ to +55℃) in operation, (-40℃ to +75℃) in storage	
Working Humidity	95% relative humidity, non-condensing	
Altitude	Up to 6000 feet (2000 m)	
Mounting Type	Wall Mount (default) / Floor post (optional accessory)	
IP Performance	IP54	
Cooling	Forced air	
Charging Cable Length	16.4 ft (5 m), straight cable	
Dimension (H x W x D, mm)	355 x 690 x 770 mm	
Net Weight	130Kg	150Kg
Network Interface	Ethernet, 4G	
OCPP	OCPP1.6J, OCPP2.0.1	
Web Portal & Mobile App	Yes, ios/Android	
Certification	CE & TUV, EU standard, DIN70121/ISO15118/IEC61851	

Dimension Details



For more product information and sales inquiries :



XIAMEN GALAXY CAMPHOL TECHNOLOGY CO.,LTD

- www.iocharger.com
- +86-592-6022509
- sales@iocharger.com
- UNIT04, 14th floor, Building A01, Software Park 3, Jimei, Xiamen, Fujian, P.R.C