

# Mini Smart AC Charger

## Key Features

### Unique Design

Direct CT connection for load balancing

### Powerful Charging Capability

Up to 32A, 40A versions available

### Smart Grid Savings

Schedule your charging times when rates are lower

### Smart Network Connectivity

Ethernet, WLAN, Bluetooth available

### Mobile App Identification

User Authentication via Bluetooth or Mobile App

## Benefits

- Easy configuration for any charging network
- Offline Bluetooth management
- OCPP 1.6J, OCPP 2.0.1
- Remote management and smart charging
- Smart Load Balancing support



# Specification

Specifications are subject to change without notice.

Input Rating	200-240V AC 1-phase
Output Rating	32A, 40A Max
Frequency(Hz)	50/60Hz
Internal RCD	Integrated, 20mA CCID
Input Cord	Hardwire/ NEMA 6-50P/ NEMA 14-50P
Electrical Protection	Over current, short circuit, over voltage, under voltage, ground fault, lightning surge, over temperature protection
Button	1 x Physical button
Indications	Standby(Blue), Charging(Flashing Blue), Fault(Red), Warning(Flash Red)
User Authentication	RFID reader optional (ISO/IEC 14443A/B)
OCPP	Full OCPP 1.6J & OCPP 2.0.1 support
Network Interface	Ethernet, WiFi, Bluetooth
Dynamic Load Balancing	Support up to 252 pcs chargers per LAN
Energy Integration	Eco-friendly with Solar & Battery storage system
Enclosure Rating	Type 3R
Charging Interface	Type-1 SAE J1772 cable
Mounting Type	Wall or post (post supplied separately)
Certifications	UL 2594:2022, UL 2231, CSA C22.2 No. 280-22

# Applications



Residential



Commercial



Multi Family