

New Pedestal Dual AC Charger

Key Features

Unique Design

7" LCD Display for excellent experience

Powerful Charging Capability

1-Phase 2x7kW & 3-Phase 2x22kW available

Current Leakage Protections

RCCB Type-B

Smart Network Connectivity


Intelligent Ethernet, Cellular, WLAN Switching

RFID & Mobile App Identification

User Authentication via RFID or Mobile App

Benefits

- Easy configuration for any charging network
- POS payment integrated
- OCPP 1.6J, OCPP 2.0.1
- ISO15118 Plug&Charge
- OCPP Smart Charging



POS Payment Integrated

Input Rating	1-phase 230V±20%	3-phase 400V±20%
Output Rating	2x7kW, 32A	2x22kW, 32A
Frequency(Hz)	50/60Hz	
Internal RCD	Type-B RCCB x 2	
Meter	CE&MID certified meter x 2	
Electrical Protection	Over current, short circuit, over voltage, under voltage, ground fault, lightning surge, over temperature protection	
Button	2 x Physical button	
Indications	Standby(White), Charging(Flashing White), Fault(Red), Warning(Flash Red)	
User Authentication	RFID reader (ISO/IEC 14443)	
OCPP	Full OCPP 1.6J & OCPP 2.0.1 support	
ISO15118 Plug & Charge	Optional	
Phase Rotation	Optional	
Network Interface	Ethernet, WiFi, 4G smart internet connection	
Display	7" LCD or 7" touch screen optional	
Dynamic Load Balancing	Support up to 252 pcs chargers per LAN	
Energy Integration	Eco-friendly with Solar & Battery storage system	
Ingress Protection	IP55, IK10	
Charging Interface	SAE J1772 & Type-2 cable/ Type-2 socket	
Certifications	CE compliant	

Applications



Workplaces



Commercial



Gas Station



Fleet



Parking



CPO